


The fastest fogging security systems












PUMP LINE



CERTIFICATIONS

UR FOG machines have been developed, thanks to the internal R&D team and laboratories, with innovative solutions for security and fully respecting internationals approvals and regulations.

The fog fluid is certified by EUROFINS, one of the largest multinational companies for chemical, cosmetic, medicine certification, as not toxic for humans and animals and the fluid content is not in contrast with any islamic country regulation. Products have been already sold in over 80 worldwide countries.



Fogging machines have EMC - FCC - CE approvals and respect EN 50131-8 regulation.











PRODUCT RANGE



FAST 250 PUMP PRO PLUS IN 250

PUMP 250

Up to 250 m³ (recommended visibility)
One bag 1000 ml included
Shot programmable in seconds
Vertical/horizontal installation
THREE INPUTS: arming, shooting
and PIR sensor validation

FOUR OUTPUTS: empty bag, fault, tamper,

shot confirmation Adjustable nozzle

TECHNICAL LIST

PUMP LINE

MAX FOG EMISSION IN A SINGLE SHOT	250 m³
MAX SECONOS IN A SINGLE SHOT	30 sec
TOTAL EMISSION WITH FULL FOG BAGS	1500 m ³
CYLINDERS OR PUMP	FOG STORM PUMP
FOG TANK CAPACITY	1 L PLASTIC BAG
WORKING TIME WITHOUT MAINS POWER	ABOUT 2 H
HEATING TIME	ABOUT 70 min.
VERTICAL MOUNTING	YES
HORIZONTAL MOUNTING	YES
SERIAL PORT FOR BUS	YES
AVERAGE POWER CONSUMPTION	37 W
BACK UP BATTERY	2 Ah
ELECTRONIC BOARD	PLUS
CABINET TYPE	PRO
FOG FLUID CERTIFIED AS NOT DANGEROUS	YES
EUROPEAN STANDARD Certifications	YES
HEATER CARTORIGE	300 W




FAST 250 PUMP PRO PLUS



Up to 250 m3 (recommended visibility)
One bag 1000 mi included
Shot programmable in seconds
Vertical/horizontal installation
THREE INPUTS: arming, shooting
and PIR sensor validation
FOUR OUTPUTS: empty bag, fault, tamper,
shot confirmation
Adjustable nozzle

The Fog Storm pump, specifically designed for glycol-based fluids, gives the PUMP line the unique flexibility needed to quickly safeguard small, medium and large volumes, up to 4000 m³. The models are equipped with security cabinets and an advanced electronic with 3 inputs and 4 outputs which recharge a standard 2 Ah battery (not included).





RECHA	RGE	VERTICAL HORIZONTAL	LIQUID QUANTITY (ml)	FOG MACHINE Model
		VERTICAL HRIZONTAL	1000	Fast 250 PUMP PRO PLUS Fast 500 PUMP PRO PLUS Fast 1500 PUMP PRO PLUS
		VERTICAL	3000 4000	Fast 250-500 PUMP PRO PLUS (WITH TOP BOX) Fast 4000 PUMP PRO PLUS Fast 1500 PUMP PRO PLUS (WITH TOP BOX)





POWER SUPPLY AND 2Ah BATTERY INSTALLED IN PUMP PRO PLUS FO GING SYSTEMS G TERY NOT INCLUDED) (BAT





me 250

FAST 250 PUMP PRO PLUS

YES

37 W

YES

YES

YES

YES

YES

YES

It is the ideal fogging system to protect small /medium areas like shops, homes, garages. When the machine is triggered it shoots for the seconds set, when the bag is empty you just replace it with a new one in a very easy way. The fluid bag covers 250 m³ in 30 seconds. It is prearranged to an easy wall installation and it has a lower compartment to equip boards or accessories if needed.



Powerful and fast fogging system, can cover up to 250 m3 in 30 seconds.



WEIGHT OF THE FOG MACHINE ABOUT 14KG WEIGHT WITH PACKAGING ABOUT 15 KG UNITS ON ONE PALLET 100X120 24 DIMENSION OF THE MACHINE 21,5X27,0XH43,5 DIMENSION OF THE PACKAGING 26,0X38,0XH53,0 COLORS WHITE WORKING TIME WITHOUT MAINS POWER **ABOUT 2HOURS** HEAT UP TIME FROM COLD ABOUT 70 MINUTES **VERTICAL MOUNTING** YES HORIZONTAL MOUNTING YES SERIAL USB PORT FOR MONITORING YES NOZZLE TAMPER YES

ALARM KIT

SERIAL BUS FOR STANDARD PROTOCOL

OPTIONAL YES NEW HEATING SYSTEM PLUS UP TO 350 m³ COVERAGE IN A SINGLE SHOT (1,5 M VISIBILITY) UP TO 250 m³ COVERAGE IN A SINGLE SHOT (RECOMMENDED DENSITY) MAX SECONDS OF FOG EMISSION 30 sec MAX FOG EMITTED WITH FULL FOG BAG $1500 \, m^3$ NUMBER OF BAG FOG TANK CAPACITY 1x 1000 ml SHOOTING SPECIFICATION PROGRAMMABLE IN SECONDS **BAG INCLUDED** ELECTRICAL SPECIFICATIONS

POWER SUPPLY 230 V or 110 V AVERAGE POWER CONSUMPTION **BACK UP BATTERY** PIR SENSOR VALIDATION INPUT SHOT CONFIRMATION OUTPUT COMPLIES WITH EUROPEAN CE FOG FLUID IS CERTIFIED



The innovative formula of the fog fluid has a high percentage of glycol which ensures an extremely dense fog.



Disposable recharge, very easy to replace, at a very competitive price.



The perfect thermal insulation allows to reduce the power consumption and also to save energy.



Exclusive patented system that allows to automatically detects if the nozzle has been obstructed by sending a signal in case of tampering.



A serial bus allows to add additional boards to each UR Fog system for an easier interface with all kinds of alarm centrals.



MEETS EUROPEAN STANDARD







UR FOG fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.



UR Fog fogging systems are certified according to the European standards, the fog fluid is tested and is absolutely safe for people, animals and objects and doesn't leave any residual.



ACCESSORIES

Bag 1000 ml

Bag 3000 ml

Bag 4000 ml

Top BOX 3000 ml

Top BOX 4000 ml

Nozzle extention 7cm

3 holes nozzle

Demo Kit

Antirobbery cable

Antirobbery button

Relay board

Arming key

Keyfob + receiver

Transceiver rs232 5/12 V

WI-FI LAN board with cloud


LAN board with cloud

Wall metal bracket

2 Handlers



ADD-ON BOARDS



Relay board

is designed to provide four relay outputs, potentially free.

LAN BOARD WITH CLOUD



Cloud LAN board to monitor fogging machines and diagnostic. Great advantage for all installers that can check from remote if any maintenance is needed.







Check the parameters of all connected machines

WI-FI LAN BOARD WITH CLOUD



WI-FI LAN BOARD

The WIFI LAN board allows wired or wireless Lan connection. Through the extremely secure Cloud service, provided for free, it allows, in addition to the systems monitoring, to remotely activate the controls of arming, shooting and setting in seconds the fogging system.



UR FOG S.r.I.

Sede legale / Legal Office : via Giacinto Collegno n°11 - 10143 Torino - Italy

Sede operativa e magazzini / Operation and delivery to : via Toscana n° 38 - 10099 San Mauro T.se (Torino) - Italy

C.F. / P. Iva 10724850010 - Reg. imprese TO - 1157030 - Numero Iscrizione Reg. AEE: IT19050000011412 Cap. Soc. Euro 10.000 int. versati Tel. +39 011 0133037 - Fax +39 011 0133005 - e-mail